Una Micro Stripe Ecotrust

Product Description

THE URGE TO EXPLORE SPACE

Product description	Methods	Product data
Construction characteristics		
Structure	ISO 2424	Woven loop pile
Pile material	DIR 96/73, 96/74	100% polyamide
Coloration	-	Solution dyed
Backing	eTL	Ecotrust 350, 100% recycled
Dimensions	ISO 3018	48x48/96x96 cm
Total thickness	ISO 1765	Apr 5,0 mm.
	.	0.20""
Total carpet weight	ISO 8543	Apr 2.400 g/m2
	.	70.8 oz./yd2
Pile yarn weight	eTL	480 g/m2
	.	14.16 oz./yd2
Soil protection	eTL	Yes
Performance characteristics		
Performance areas	EN15114	Class 33 - Commercial - Heavy
Guarantee	eTL	Contract certificate
Castor chair suitability	eTL	Intensive use
Suitability for use on stairs	eTL	Yes
Static control	eTL	Permanently antistatic
Acou.insu. from impact noice	eTL	16 dB
Acoustical absorption	eTL	0,20 aW
Suitability underfloorheating	eTL	Apr 0,09 m2K/W
Light reflectance	eTL	Testreport
Colour fastness to light	ISO 105-B02	>5
	AATCC 16	5.0
Colour fastness to rubbing wet	ISO 105-X12	>3
	AATCC 165	5.0
Colour fastness to rubbing dry	ISO 105-X12	>3-4
	AATCC 165	5.0
Colourfast. to water patterned	ISO 105-E01	>4
Cleaning	AATCC 138	5.0
Colour fastness to ozone	AATCC 129	5.0
Colour fast.Oxides of nitrogen	AATCC 164	5.0
Other performance tests	ASTM D5252 Hexapod	5.0/ 5.0
	-	Commercial - Heavy
	AATCC 134 Electrost.propensity	0.8 kV
Safety & Environment		
Fire classification	MK GODKENDELSE	Approved
	DIBT AbZ.no.	Z-156.601-675
	ASTM E-648	Class 1
	ASTM E662 Smoke Density	<450
	ASTM D2859 Surface Flamm.	Pass
	EN 13501-1 Euroclass	Bfl-s1
	RUSSIA	Approved
CE Labeling	EN 14041	Certified
	CPR	1021-CPR-010-1/16

ege
THE URGE TO EXPLORE SPACE

Product description	Methods	Product data
	Declaration of Performance	DOP 5B-PA-ECT350
	Notified body no.	1021
	Ce Year	14
	Content of PCP EN 12673	DL
	Formaldehyde emission	NA
	Slip resistance EN 13893	Class DS
Indoor climate	DIM certificate	No. 006
	Green Label Plus	Approved
	Emissions dans l'air intérieur	A+/A+
	GECA	Approved
Environment	BREEAM-NOR	With ECTA Backing
	Environmental Product Decl.	EPD-EGE-20140127-CBC1-EN
	Cradle To Cradle Certified	Ecotrust, bronze Certified
	Recycled Content, ISO 14021	Apr 15,0 %
	Recycled Content for LEED	Apr 15,0 %
	LEED	Qualified

Guides

Installation + adhesive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Installation tiles	Direction of installation	Quarter turn
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

Manufacturer characteristics

Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	DS/OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK
	TransQ	Qualified